



ISO 4014
Sechskantschrauben mit Schaft
Edelstahl A2

VPE in Stk. = bestellbare Verpackungseinheiten

d1	M 5	M 6	M 8	M 10	M 12	M 14	M 16	M 18	M 20	M 22	M 24
l/mm	VPE	VPE	VPE	VPE	VPE	VPE	VPE	VPE	VPE	VPE	VPE
25	1 / 200										
30	1 / 200	1 / 200	1 / 200								
35	1 / 200	1 / 200	1 / 200	1 / 200							
40	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200						
45	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200					
50	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200				
55	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200				
60	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200				
65	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200		
70	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	
75	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	
80		1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200
85		1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200
90		1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200
95		1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200
100		1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200
110		1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200
120		1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200
130		1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200
140		1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200
150		1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200
160			1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200
170				1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200
180				1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200
190				1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200
200				1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200	1 / 200
k	3,5	4	5,3	6,4	7,5	8,8	10	11,5	12,5	14	15
Antrieb	SW 8	SW 10	SW 13	SW 16	SW 18	SW 21	SW 24	SW 27	SW 30	SW 34	SW 36

k = Kopfhöhe
L = Länge in mm
SW = Schlüsselweite
b = nach Norm

Maße in mm

[Link zum Produkt](#)

