


Art.-Nr. 60208-1029-

Gelenkbolzenschelle

Edelstahl A2 und A4



Schlauch Ø	B	Max. Drehmoment (Nm)	Max. Druck (Bar)	Antrieb (sw)		
17-19	18	10	40	8		
19-21	18	10	40	8		
21-23	18	10	40	8		
23-25	18	10	40	8		
25-27	18	10	40	8		
27-29	18	10	40	8		
29-31	20	12	35	11		
31-34	20	12	35	11		
34-37	20	12	35	11		
37-40	20	12	35	11		
40-43	20	12	35	11		
43-47	20	12	35	11		
47-51	20	16	30	11		
51-55	20	16	30	11		
55-59	20	16	30	11		
59-63	20	16	30	11		
63-68	20	16	30	11		
68-73	25	30	20	13		
73-79	25	30	20	13		
79-85	25	30	20	13		
85-91	25	30	15	13		
91-97	25	30	15	13		
97-104	25	30	15	13		
104-112	25	30	10	13		
112-121	25	30	10	13		
121-130	25	30	10	13		
130-140	28	45	6	15		
140-150	28	45	6	15		
150-162	28	45	6	15		
162-174	28	45	3	15		
174-187	28	5	3	15		
187-200	28	45	3	15		
200-213	28	45	3	15		
213-226	28	45	3	15		
226-239	28	45	3	15		
239-252	28	45	3	15		

Maße in mm

Diesen Artikel können Sie [HIER bestellen.](#)